



IA-200a 100W AC Adaptor

PROSeries



The IA-200a is a dual output 100W AC adaptor. The combination of reliable operation and a compact space saving design gives the IA-200a the competitive edge, especially when used on location or in the production studio. Even with its rugged metal enclosure the IA-200a is lightweight, so minimum effort is needed to pick up, prepare to use and store for transport.

The IA-200a is primarily used to power portable ENG cameras, but is also a proven power source for a wide range of camera lights, portable monitors and other broadcast equipment. It also offers complete peace of mind in terms of safety, with automatic overload protection just one of the safety features integral to the IA-200a.

IA-200a Product Features:

- **100W 13.8V DC output** via 2 x 4-pin XLR connector.
- **2 x XLR outputs** will draw 100W in combination from two channels, or 100W from a single channel.
- **The IA-200a weighs just under 3 lbs. in** an all-purpose rugged metal enclosure. An integrated carry handle is provided for easy hand carriage.
- **Internal safety features** protect the IA-200a from overload damage should an excessive load be drawn. It does this by automatically shutting down to recover. The IA-200a PSU produces 'low ripple noise' to reduce the chances of signal interference with nearby devices.
- **Universal AC input voltage** for worldwide operation.

Technical Specification

Input:

AC 100~240V 50/60Hz

Power Consumption:

258VA max. (242VA:100V / 258VA:240V)

DC Output:

100W max., 13.8V

DC Output Connector:

4-pin XLR connector

Dimensions:

4.53(W) x 1.97(H) x 10.63(D) inches

Weight:

2.87 lbs. approx.

IDX System Technology, Inc.
19001 Harborage Way, Suite 105
Torrance, CA 90501
U.S.A.
Telephone: (310) 328-2850
Fax: (310) 328-8202



For further information, email us: idx.usa@idx.tv or visit our website www.idxtek.com
IDX reserves the right to change the specifications contained herein without notice.