



							
		E-7/ E-7S	E-HL9/ E-HL9S	DUO-95	E-10/ E-10S	ELITE	DUO-150
		68Wh	87Wh	91Wh	93Wh	136Wh	146Wh
VL-PVC1	1ch	270	340	354	360	520	569
VL-2PLUS	1ch	180	180	210	220	290	310
	2ch	360	360	420	440	580	620
VL-2SPLUS	1ch	140	105	135	145	185	205
	2ch	140	135	170	165	225	255
VL-4S	1ch-3ch	155	140	170	180	240	255
	4ch	180	175	210	220	290	310
VL-4Si	1ch-3ch	155	140	170	180	240	255
	4ch	180	175	210	220	290	310
VAL-4Si	1ch-3ch	155	140	170	180	240	255
	4ch	180	175	210	220	290	310

Note: Charge times displayed in minutes

All ENDURA V-Mount Batteries are compatible with ENDURA Chargers
 All ENDURA V-Mount chargers are worldwide compatible with input voltages ranging from AC100-240V

For service and support, please contact us at service.usa@idx.tv or 310-328-2850

IDX System Technology, Inc.
 19001 Harborage Way, Suite 105
 Torrance, CA 90501 USA
 Telephone: (310) 328-2850
 Fax: (310) 328-8202

