

PSG6 INVERTER GENERATOR



Studio grade power solutions.



The unique **PSG6** delivers 6,500 watts of dependable, sound attenuated power in a package designed especially for the film industry. Studio professionals will appreciate the exclusive features provided by **Multiquip** such as a rugged 1½-inch pipe frame protection and standard Bates connector. This environmentally friendly unit consumes less fuel than comparable generators and its low noise level makes it ideal for any production environment.

- **Inverter type** generator provides stable power for computers and sensitive electronic equipment.
- **Easy starting** is provided by a Honda GX390 engine equipped with electric start.
- **Low oil shutdown** to prevent engine damage.
- **Heavy-duty** foam filled tires enable the unit to roll easily over rough or uneven terrain. A hand brake on grade, secures the unit.
- **ECO-Throttle** reduces fuel consumption and allows for up to 14 hours of run time on one tank of fuel..
- **Standard Bates connector**— exclusive from Multiquip— 60 Amp connection to fit your equipment requirements. Duplex and twist-lock receptacles are standard.
- **LCD control panel** provides a digital readout for performance and service diagnosis.
- **Rugged frame** constructed of 1½" diameter steel pipe protects the generator shell from damage.
- **Super quiet** operation produces only 60dB at rated load.



Control panel featuring Bates connector and Honda iMonitor®

| Model                     | PSG6                                                            |
|---------------------------|-----------------------------------------------------------------|
| Engine                    | Honda GX390 Single cylinder, overhead valve, air cooled         |
| Displacement              | 389cc                                                           |
| AC Output                 | 120/240V<br>6500W max. (54.1/27.1A)<br>5500W rated (45.8/22.9A) |
| Receptacles               | (2) 5-20P, (1) L5-30P, (1) L14-30P, (1) 60 A Bates              |
| Starting Systems          | Recoil, electric*                                               |
| Fuel Tank Capacity gal.   | 4.5                                                             |
| Run Time Per Tank         | 4.7 hrs. @rated load,<br>14.0 hrs. @1/4 load                    |
| Dimensions (LxWxH) inches | 34.5 x 28 x 32                                                  |
| Noise Level               | 60 dB @ rated load<br>53 dB @1/4 load                           |
| Dry Weight                | 326 lbs                                                         |

\*Battery included



Hinged panels provides easy service access



Hand Brake safely secures the unit on grade

© COPYRIGHT 2013, MULTQUIP INC.

Your Multiquip dealer is:

Connect with us on



Call us today - 800-421-1244



www.multiquip.com