



## VM-2HD

1:2 HD-SDI Video Distribution Amplifier

---



The VM-2HD is a high-performance distribution amplifier for HD-SDI signals. It takes one input, provides reclocking and equalization and distributes the signal to two identical outputs

### FEATURES

---

**Max. Data Rate** - Up to 1.485Gbps

**HDTV Compatible**

**Multi-Standard Operation** - SDI (SMPTE 259M/344M) & HD-SDI (SMPTE 292M)

**Kramer Equalization & re-Klocking™ Technology** - Rebuilds the digital signal to travel longer distances

**HD-SDI & SDI Input Indication LEDs**

**Ultra Compact Pico TOOLS™** - 4 units can be rack mounted side-by-side in a 1U rack space with the optional RK-4PT rack adapter



# KRAMER

## TECHNICAL SPECIFICATIONS

INPUT:	1 SMPTE-259M/292M/344M SDI, 75Ω on a BNC connector
OUTPUTS:	2 equalized and reclocked SMPTE-259M/292M/344M outputs 75Ω on BNC connectors
MAXIMUM DATA RATE:	1.485Gbps
MAX. OUTPUT LEVEL:	800mVpp/75Ω
COUPLING:	AC
POWER CONSUMPTION:	12V DC, 250mA
INCLUDED ACCESSORIES:	Power supply, mounting bracket
OPTIONS:	RK-4PT 19" rack adapter
PRODUCT DIMENSION:	6.22cm x 5.18cm x 2.44cm (2.45" x 2.04" x 0.96" ) W, D, H
PRODUCT WEIGHT:	0.1kg (0.2lbs) approx
SHIPPING DIMENSION:	23.20cm x 13.60cm x 10.00cm (9.13" x 5.35" x 3.94" ) W, D, H
SHIPPING WEIGHT:	0.5kg (1.1lbs) approx

